


VERSAPRINTER™ & LABELIZER® PLUS TAPE CARTRIDGES

BRADY INDOOR/OUTDOOR VINYL TAPE - B-580

Our most popular tape, adheres well to pipes, walls, equipment, windows... most clean, dry surfaces. It even conforms well to irregular, curved or rough surfaces. For industrial use: stands up to grease, oil and most industrial chemicals. Five-year average outdoor durability in temperatures from -40°C to 82°C. Tape can be applied as low as -18°C. Your best selection of label colour and type colour options including those that meet ASME (ANSI) Standards. 27.4 metres per cartridge.

Size	Part Number			Qty Per Pkg.
	Black	White	Red	
13mm x 27.4m	64624	64628	64632	2
28.6mm x 27.4m	64625	64629	64633	2
57.1mm x 27.4m	64626	64630	64634	1
100mm x 27.4m	64627	64631	64635	1



Size	Part Number														Qty Per Pkg.
	Black	Black	White	White	Red	White	Black	Magenta	Black	Black	White	White	White	White	
13mm x 27.4m	64687	64810	64814	64818	64790	64822	64826	64794	64830	64878	64882	-	64890	64894	2
28.6mm x 27.4m	64688	64811	64815	64819	64791	64823	64827	64795	64831	64879	64883	64887	64891	64895	2
57.1mm x 27.4m	64689	64812	64816	64820	64792	64824	64828	64796	64832	64880	64884	64888	64892	64896	1
100mm x 27.4m	64690	64813	64817	64821	64793	64825	64829	64797	64833	64881	64885	64889	64893	64897	1



The 3 Globalmark systems replace the LabelizerPlus, VersaPrinter and GraphicsPro. - which have been discontinued. A list of supplies for these older systems is available from www.bradyaust.com.au or in your pricelist. Brady is committed to supplying consumables for these printers now and into the future.

BRADY HI-PERFORMANCE POLYESTER TAPE - B-569

Great for many industrial applications. Tape applies nicely to smooth surfaces. Has the durability of the B-580 indoor/outdoor vinyl tape sold above. Service temperatures from -40°C to 100°C with minimum application temperatures of -18°C. Tape is specially designed with a low halide content which means it's great for use on stainless steel and nickel piping. Tape comes in 11 colour combinations and 4 widths. Generous 33m per cartridge.

Size	Part Number												Qty Per Pkg.
	Black	Magenta	White	White	White	White	White*	Black*	Red*	Black	Red		
13mm x 33m	64326	64304	64330	64334	64338	64308	64342	64346	64350	64354	64358	2	
28mm x 33m	64327	64305	64331	64335	64339	64309	64343	64347	64351	64355	64359	2	
57.1mm x 33m	64328	64306	64332	64336	64340	64310	64344	64348	64352	64356	64360	1	
100mm x 33m	64329	64307	64333	64337	64341	64311	64345	64349	64353	64357	64361	1	


* On Clear Tape.

REFLECTIVE TAPE - B-584

Well suited for both indoor and outdoor applications. The reflective capabilities are ideal for reading barcodes on racks and shelves from long distances, as well as on vehicles, work sites, low-light areas and more. Available in three high visibility colours. Cartridge contains up to 23m of tape. Service temperatures from -40°C to 70°C with a four to six year average outdoor life.

Size	Part Number		Qty Per Pkg.
	Black	Black	
28.1mm x 23m	64739	64403*	2
57.1mm x 23m	64740	64404**	1
100mm x 23m	64741	64405	1

* Tape is 21m per roll ** Tape is 17.6m per roll



Now is the time to update your old printer to the latest technology, with great new features & functionality. Call for demo & quote

BRADYGLO™ LUMINOUS TAPE - B-582

Brady B-582 is used for exit and directional signs, identification of fire alarms and extinguishers, low location egress pathway markings, and directional systems for escape or evacuations route in accordance with ASTM 2030-99: Recommended Uses of Photoluminescent Safety markings. It is a non-toxic, non-radioactive and explosion safe material which allows for general sanitary disposal.

Meets and/or exceeds several International and Maritime Standards.

Requires a charge time of five minutes at 1000 Lux. Consistent glow life and unlimited recharability throughout service life of years indoors (not recommended for outdoors). Service temperature of -40°C to 80° C.

Size	Part Number				Qty Per Pkg.
	Black	Red	Blue	Green	
28.1mm x 23m	64743	64784	46339	46342	2
57.1mm x 23m	64744	64785	46340	46343	1
100mm x 23m	64745	64786	46341	46344	1



- Glows in a totally dark room for at least 10 hours
- Meets ISO, DIN and ASTM standards.