


IDXPERT™ LABEL CARTRIDGES

WIRE AND CABLE MARKERS - ADHESIVE WRAP AROUND

Vinyl Cloth Material (B-498)

Ideal for wrapping wires and cable. Aggressive tack adhesive but still repositionable. Temperature Range: -40°C to 70°C.




Wire Gauge*	Max. Wire Diameter	Part Number	Diagram	Reference	Labels per Cartridge	Dimensions A (mm)	B (mm)	Colour
12-16 Gauge	2.80 mm max dia	60457	★	X-7-498	300	12.70	12.70	BK on WT
16-10 Gauge	4.00 mm max dia	60458	★	X-11-498	275	12.70	19.05	BK on WT
12-10 Gauge	5.00 mm max dia	102727	★	X-163-498	225	12.70	25.40	BK on WT
12-10 Gauge	5.00 mm max dia	60459	★	X-18-498	225	19.05	25.40	BK on WT
12-10 Gauge	5.00 mm max dia	60460	★	X-19-498	200	25.40	25.40	BK on WT
10-4 Gauge	7.00 mm max dia	102728	★	X-162-498	165	12.70	38.10	BK on WT
10-4 Gauge	7.00 mm max dia	60461	★	X-103-498	200	25.40	31.75	BK on WT
10-4 Gauge	7.00 mm max dia	102729	★	X-31-498	200	25.40	38.10	BK on WT
3 Gauge-2/0	14.00 mm max dia	102726	★	X-21-498	95	25.40	63.50	BK on WT
3/0-400 kcmil	22.00 mm max dia	102725	★	X-23-498	60	25.40	101.60	BK on WT

*Approx. based on AWG for THHN wire.

WIRE AND CABLE MARKERS - SELF LAMINATING

Vinyl Self-Laminating Material (B-427)

Resistant to water, oil, solvents and abrasion. Temperature Range: -70°C to 70°C. UL recognised.




Wire Gauge*	Max. Wire Diameter	Part Number	Diagram	Reference	Labels per Cartridge	Dimensions A (mm)	B (mm)	C (mm)	Colour
16-10 Gauge	4.00 mm max dia	60089	▶	XSL-11-427	500	12.70	19.05	9.53	BK on WT
16-10 Gauge	4.00 mm max dia	60090	▶	XSL-96-427	250	25.40	19.05	9.53	BK on WT
12-10 Gauge	5.00 mm max dia	60091	▶	XSL-17-427	500	12.70	25.40	9.53	BK on WT
12-10 Gauge	5.00 mm max dia	60092	▶	XSL-18-427	250	19.05	25.40	9.53	BK on WT
12-10 Gauge	5.00 mm max dia	60093	▶	XSL-19-427	250	25.40	25.40	9.53	BK on WT
10-4 Gauge	7.00 mm max dia	60169	▶	XSL-102-427	250	12.70	31.75	9.53	BK on WT
10-4 Gauge	7.00 mm max dia	60338	▶	XSL-103-427	250	25.40	31.75	12.70	BK on WT
10-4 Gauge	7.00 mm max dia	60339	▶	XSL-115-427	250	38.10	31.75	12.70	BK on WT
10-4 Gauge	8.00 mm max dia	60340	▶	XSL-29-427	450	12.70	38.10	12.70	BK on WT
10-4 Gauge	8.00 mm max dia	60341	▶	XSL-30-427	250	19.05	38.10	12.70	BK on WT
10-4 Gauge	8.00 mm max dia	60342	▶	XSL-31-427	250	25.40	38.10	12.70	BK on WT
10-4 Gauge	8.00 mm max dia	60529	▶	XSL-31-427-YL-BK	250	25.40	38.10	12.70	BK on YL
10-4 Gauge	8.00 mm max dia	60343	▶	XSL-32-427	225	38.10	38.10	12.70	BK on WT
3 Gauge-2/0	14.00 mm max dia	60344	▶	XSL-21-427	100	25.40	63.50	19.05	BK on WT
3 Gauge-2/0	14.00 mm max dia	60527	▶	XSL-21-427-YL-BK	100	25.40	63.50	19.05	BK on YL
3 Gauge-2/0	14.00 mm max dia	60345	▶	XSL-116-427	100	38.10	63.50	19.05	BK on WT
3/0-400 kcmil	22.00 mm max dia	60347	▶	XSL-23-427	85	25.40	101.60	25.40	BK on WT
3/0-400 kcmil	22.00 mm max dia	60538	▶	XSL-23-427-YL-BK	85	25.40	101.60	25.40	BK on YL
3/0-400 kcmil	22.00 mm max dia	60438	▶	XSL-33-427	85	38.10	101.60	25.40	BK on WT
500-900 kcmil	33.00 mm max dia	60439	▶	XSL-34-427	50	38.10	152.40	38.10	BK on WT

*Approx. based on AWG for THHN wire.

WIRE AND CABLE MARKERS - FLAGS

Nylon Cloth Material (B-499)

Permanent adhesive. Pliable for rough or smooth surfaces. Temperature Range: -70°C to 90°C. UL recognised.



Material Notes	Part Number	Diagram	Reference	Labels per Cartridge	Dimensions A (mm)	B (mm)	C (mm)	Colour
Standard Flag <i>approx. 25 x 25mm resulting flag size</i>	105877	★	XF-151-499	115	25.40	25.40	6.350	BK on WT
Low Profile Flag <i>approx. 12 x 38mm resulting flag size</i>	105878	★	XF-152-499	200	38.10	12.70	6.350	BK on WT

