

PERFORMANCE & QUALITY YOU CAN TRUST

CONTINUOUS TAPES



INDOOR/OUTDOOR VINYL TAPE B-580/B-588

- Adheres to most clean, dry surfaces
- Also conforms well to irregular, curved or rough surfaces
- Stands up to grease, oil and most industrial chemicals
- 5-year average outdoor durability in temperatures from -40°C and +82°C (under certain conditions*)
- Tape can be applied at as low as -18°C



MINIMARK™ INDOOR/OUTDOOR VINYL TAPE B-7589

- Adheres to most clean, dry surfaces
- Also conforms well to irregular, curved or rough surfaces
- Stands up to grease, oil and most industrial chemicals
- 3-year average outdoor durability in temperatures from -40°C and +82°C (under certain conditions*)



MINIMARK™ INDOOR VINYL TAPE B-7591

- Preferred in logistics market
- Economical/Non-UV stabilised




HI-PERFORMANCE POLYESTER TAPE B-569

- Adheres to smooth surfaces
- Low halide content: ideal for use on stainless steel and nickel piping
- 3-year average outdoor durability in temperatures from -40°C to +100°C (under certain conditions*)
- Tape can be applied as low as -18°C



REFLECTIVE TAPE B-584

- Ideal for reading labels in low light conditions (with flashlight)
- 5-year average outdoor durability (under certain conditions*)
- Usage from: -40°C up to +80°C
- Application Temperature: minimum +10°C



COLD TEMPERATURE TAPE B-549

- Stands up to chemicals, water, oil and some solvents
- Usage from: -40°C up to +80°C
- Application Temp: minimum -23°C



ECONOMY POLYPROPYLENE TAPE B-529

- Ideal low-cost choice
- Usage from: -40°C up to +80°C
- Application Temp: minimum +10°C

DIE-CUT LABELS



MINIMARK™ DIRECT THERMAL PAPER B-7604

- No ribbon required
- Economical solution



MINIMARK™ THERMAL TRANSFER PAPER B-7608

- Variety of sizes
- Suitable for shipping, warehousing



SELF LAMINATING WIRE ID B-427

- RoHS compliant
- Durable wire and cable identification




REPOSITIONABLE VINYL TAPE B-581

- Special adhesive allows easy removal and re-application
- 5-year average outdoor durability in temperatures from -40°C to +80°C (under certain conditions*)
- Application Temp: minimum +10°C



PHOTOLUMINESCENT B-526/B-582

- Will remain clearly visible in a totally dark room for at least one hour! (High performance Brady Glo now available)
- Indoor use only
- Usage from -40°C up to +80°C
- Application Temp: minimum +10°C




TAMPER RESISTANT TAPE B-530

- Destructs into tiny fragments when tampered with making removal very tedious and difficult
- 3-year average outdoor durability (under certain conditions*)
- Usage from: -40°C up to +80°C
- Application Temp: minimum +10°C



STATIC CLING TAPE B-515

- Ideal for frequent repositioning
- Usage from: -40°C up to +80°C
- Application Temperature: minimum +10°C
- Indoor use only



BRUSHED GOLD POLYESTER B-575

- 2-year average outdoor durability (under certain conditions*)
- Usage from: -40°C up to +150°C
- Application Temperature: minimum +10°C



OVERLAMINATE B-674

- Rolls of overlaminating providing improved label durability
- 2-year average outdoor durability (under certain conditions*)
- Usage from: -40°C up to +150°C
- Application Temperature: minimum +10°C




MAGNETIC TAPE B-509



NON ADHESIVE TAG STOCK B-551



METALLISED POLYESTER TAPE B-565




MINIMARK™ STANDARD POLYESTER B-8423

- Durable labelling
- Usage from -40°C to 120°C



MINIMARK™ METALLISED POLYESTER B-7563

- Durable asset identification
- Rating plates
- Name plate quality



MINIMARK™ TAMPER EVIDENT METALLISED POLYESTER B-438

- Leaves a checkerboard footprint if removed
- Durable asset identification
- Rating plates
- Name plate quality

* Depends on climatic conditions, colours and usage.